

[54] **KEYBOARD SWITCH AND UNITIZED  
MULTIPLE SWITCH CONFIGURATION**

[75] Inventor: **John F. Brady**, Clifton, N.J.

[73] Assignee: **Universal Technology, Inc.**, Verona,  
N.J.

[22] Filed: **Aug. 2, 1971**

[21] Appl. No.: **168,053**

[52] U.S. Cl. .... **200/5 A, 200/159 A, 200/166 CT**

[51] Int. Cl. .... **H01h 13/52**

[58] Field of Search .... **200/5 R, 5 A, 6 BB,  
200/159 R, 159 A, 159 B, 166 CT, 11 G, 166  
BH**

[56] **References Cited**

**UNITED STATES PATENTS**

2,994,531	8/1961	Eberwein .....	200/5 A UX
3,590,195	6/1971	Driver .....	200/159 B
3,614,702	10/1971	Vargas .....	200/166 CT

1,752,149	3/1930	Clurman .....	200/11 G
2,964,986	12/1960	Johnson .....	200/5 A X
3,290,439	12/1966	Willcox et al. ....	200/5 A X
2,848,567	8/1958	Estoppey et al. ....	200/11 G

*Primary Examiner*—J. R. Scott

*Attorney*—Willis H. Taylor, Jr. et al.

[57] **ABSTRACT**

A unitized configuration including plurality of key top switches. A single unit shell overlies and is secured to a circuit board upon which the contact leaves for the various switches are so mounted as to be cantilevered over their respective printed contacts. The plungers associated with the several key tops pass through openings in the shell and are biased out of contact with the underlying cantilevered leaves by spring means. Depressing of the key tops drives the plungers downward to deflect the respective contact leaves and close the associated circuits.

**21 Claims, 5 Drawing Figures**

